

S T A T E

O F

T E N N E S S E E

March 1, 2006

(Rev. 2-10-97) GAN

SPECIAL PROVISION

REGARDING

BITUMINOUS PLANT MIX MATERIALS TRANSFER DEVICE (MTD)

A Material Transfer Device (MTD) capable of unloading a truck or trailer load of hot mix asphalt without moving the truck shall be utilized when placing all asphalt mixes, including shoulder mixes, with the exception that it shall not be required when placing "CS" Mix. The MTD shall have a minimum storage capacity of 13.6 metric tons(15 tons.) It shall be equipped with mixing augers in the bottom of the storage hopper, capable of remixing or reblending the material as the material is removed from the storage hopper. Mixing augers shall be operational and utilized at all times during placement of the asphalt mixes. The MTD will have a rear discharge conveyor that swivels a minimum of 150° to allow feeding the paving machine from the front, side or rear.

The paver being fed by the MTD shall have a stationary surge hopper inserted into the paving hopper. The stationary surge hopper shall be considered as part of the MTD and shall have sloping sides (minimum of 60° from horizontal) and a minimum storage capacity of 13.6 metric tons(15 tons).

No direct payment will be made for the MTD and all cost of furnishing and/or operation of this equipment will be included in other items.